

Pipe						CDN		
						NEW	API PREMIUM	
Pipe size	<i>in</i>	4.500	<i>mm</i>	114.3	OD	<i>mm</i>	114.3	110.9
Pipe weight	<i>lb/ft</i>	16.60	<i>kg/m</i>	24.70	Thickness	<i>mm</i>	8.6	6.8
Upset Type		IEU			X-Sec Area	<i>cm²</i>	28.4	22.4
Tube grade		S135			Section Modulus	<i>cm³</i>	70.0	54.8
Range		2			Polar Section Modulus	<i>cm³</i>	140.0	109.7
Tube Yield	<i>MPa</i>	931			Tensile Yield	<i>kdaN</i>	265	208
ID	<i>mm</i>	97.2			Torsional Yield	<i>ft-lbs</i>	55,500	43,500
					80% Torsional Yield	<i>ft-lbs</i>	44,400	34,800
					Internal Pressure Yield	<i>MPa</i>	122.0	111.7
					Collapse Yield	<i>MPa</i>	115.8	75.8
					D/t		13.35	16.19
					Connection/Tube Torsional Ratio		0.781	

Tool Joint						CDN		
						NEW		
Connection Type		430 DUO			OD	<i>mm</i>	133.4	
Material Yield Strength	<i>MPa</i>	896			Tensile Yield Strength	<i>kdaN</i>	368	
OD	<i>mm</i>	133.4			Torsional Yield Strength	<i>ft-lbs</i>	43,400	
ID	<i>mm</i>	76.2			Recommended Makeup Torque	<i>ft-lbs</i>	26,000	
Pin Shoulder Angle	<i>deg</i>	18			Maximum Makeup Torque	<i>ft-lbs</i>	28,200	
Pin Tool Joint Length	<i>mm</i>	356						
Box Tool Joint Length	<i>mm</i>	356						

Drill Pipe Assembly						CDN		
					Shoulder-Shoulder Length	<i>m</i>	9.60	
					Adjusted Weight	<i>kg/m</i>	27.20	
					Closed End Displacement	<i>L/m</i>	10.57	<i>m³/m</i> 0.01057
					Open End Displacement	<i>L/m</i>	3.47	<i>m³/m</i> 0.00347
					Fluid Capacity	<i>L/m</i>	7.10	<i>m³/m</i> 0.00710
					Drift Size	<i>mm</i>	73.0	


The information contained in this data sheet and other attached documentation is for reference use only. It is not intended to imply any explicit recommendation regarding processes, procedures, or performance of the end product. It is the responsibility of the end user to verify and determine the appropriate use of the technical information - no expressed or implied warranty by Complete Tubular Products is intended.

Calculations are based on uniform wall thickness and outside diameter – no safety factor has been applied. The information provided for inspection classes is based on uniform wear and is not intended to recommend or confirm operational limits of any used product. It is recommended that drilling torque not exceed 80% of the makeup torque, however it is the responsibility of the end user to determine the acceptable use of the end product including appropriate performance ratings and safety factors where applicable. All connection torque calculations have been performed using a thread compound friction factor of 1.0. Complete Tubular Products does not endorse any specific thread compound and waives all responsibility in determining appropriate makeup torque values for any specific drilling circumstance. Modifying makeup torque values for any reason shall be done at the end users discretion and risk.

The information in this publication is subject to change without notice, please contact Complete Tubular Products for the latest publication


Makeup Torque Then Tension Chart

CDN



Connection Wear Chart

CDN



CONNECTION OD (mm)	MAXIMUM MAKEUP TORQUE (ft-lbs)
133.4	28,200
131.8	26,600
130.2	25,100
128.6	23,500
127.0	22,000
125.4	20,500
123.8	19,100
122.2	17,700
120.7	16,300
MIN REC OD (mm)	125.4
	20,600

The information contained in this data sheet and other attached documentation is for reference use only. It is not intended to imply any explicit recommendation regarding processes, procedures, or performance of the end product. It is the responsibility of the end user to verify and determine the appropriate use of the technical information - no expressed or implied warranty by Complete Tubular Products is intended.

Calculations are based on uniform wall thickness and outside diameter – no safety factor has been applied. The information provided for inspection classes is based on uniform wear and is not intended to recommend or confirm operational limits of any used product. It is recommended that drilling torque not exceed 80% of the makeup torque, however it is the responsibility of the end user to determine the acceptable use of the end product including appropriate performance ratings and safety factors where applicable. All connection torque calculations have been performed using a thread compound friction factor of 1.0. Complete Tubular Products does not endorse any specific thread compound and waives all responsibility in determining appropriate makeup torque values for any specific drilling circumstance. Modifying makeup torque values for any reason shall be done at the end users discretion and risk.

The information in this publication is subject to change without notice, please contact Complete Tubular Products for the latest publication